

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) An extreme ultraviolet light source target characterized in that a laser absorption region and an extreme ultraviolet light emission region are set close in space by adjusting a density of the extreme ultraviolet light source target.
2. (Original) The extreme ultraviolet light source target according to claim 1, characterized in that the laser absorption region and the extreme ultraviolet light emission region overlap in space.
3. (Currently Amended) The extreme ultraviolet light source target according to - Claim 1, characterized in that ~~it~~ the extreme ultraviolet light source target is is made of heavy metal or heavy-metal compound, and a density of the heavy metal or the heavy-metal compound is 0.5% to 80% of a crystal density of the heavy metal or the heavy-metal compound.
4. (Original) The extreme ultraviolet light source target according to claim 3, characterized in that the heavy metal is one among Ge, Zr, Mo, Ag, Sn, La, Gd and W, or the heavy-metal compound is one among Ge, Zr, Mo, Ag, Sn, La, Gd and W.
5. (Currently Amended); The extreme ultraviolet light source target according to ~~claim~~ claim 4, characterized in that the heavy metal is Sn or the heavy-metal compound is SnO₂.
6. (Previously Presented) The extreme ultraviolet light source target according to - Claim 1, characterized in that the target is shaped a tape.

7. (Currently Amended) The extreme ultraviolet light source target according to - Claim 1, characterized in that ~~it~~ the extreme ultraviolet light source target is made of frost of gas target having a density 0.5 to 80% that of a solid of the gas target.
8. (Previously Presented) A method of generating extreme ultraviolet light, characterized in that the extreme ultraviolet light source target according to - Claim 1 is irradiated with a laser beam.
9. (Previously Presented) An extreme ultraviolet light source, characterized by comprising the extreme ultraviolet light source target according to - Claim 1 and a laser light source irradiating the target with a laser beam.
10. (Previously Presented) The extreme ultraviolet light source according to claim 9, characterized in that the laser light source is a light source which emits a fundamental wave or a harmonic wave of YAG laser or excimer laser.
11. (Previously Presented) An extreme ultraviolet light source comprising:
a hopper having an outlet from which frost can be discharged;
a freezing machine for cooling the hopper;
a heater which can heat a wall of the hopper intermittently; and
a vacuum chamber for keeping around the hopper in a vacuum state and having a first window for guiding a laser beam from the outside to the vicinity of the outlet, and a second window for taking out extreme ultraviolet light.

12. (Original) The extreme ultraviolet light source according to claim 11, characterized in that the heater works with the principle of high-frequency discharge.

13. (Original) The extreme ultraviolet light source according to claim 12, characterized in that a plurality of discharge electrodes of the heater are provided in an outer circumference of the hopper.

14. (Currently Amended) The extreme ultraviolet light source according to - Claim 11, characterized in that ~~it~~ the extreme ultraviolet light source further comprises a bladed wheel having a plurality of blades radiating outward and rotatably fixed to the hopper just above the outlet, and in that the hopper is formed cylindrically just above the outlet so as to surround the bladed wheel.

15. (Original) A method of manufacturing an extreme ultraviolet light source target, characterized in that a density of the heavy-metal oxide of the target is made to be 0.5% to 80% of a crystal density of a heavy-metal oxide,

with a process comprising:

a step of manufacturing a gel containing a heavy-metal oxide by solving a heavy-metal chloride in dehydrated alcohol and mixing this with water; and

a step of drying the gel.

16. (Currently Amended) A method of manufacturing an extreme ultraviolet light source target, characterized in that a density of the heavy-metal oxide of the target is made to be 0.5% to 80% of a density of a heavy-metal oxide crystal

with a process comprising:

a step of manufacturing a gel containing a heavy-metal oxide by solving a heavy-metal chloride in dehydrated alcohol and mixing this with water; and

a step of forming a target by mixing the gel with nanoparticles of polystyrene and heating ~~it~~ the gel to a temperature which is 240°C or more but below a decomposition temperature of the heavy-metal oxide.

17. (Previously Presented) The method of manufacturing of the extreme ultraviolet light source target according to - Claim 15, characterized in that the heavy-metal chloride is SnCl_4 .

18. (New) The extreme ultraviolet light source target according to claim 1, characterized in that the extreme ultraviolet light source target is a solid body of heavy metal or heavy-metal compound including voids.

19. (New) The extreme ultraviolet light source target according to claim 1, characterized in that the extreme ultraviolet light source target is an aerogel body of heavy metal or heavy-metal compound.

20. (New) The method of manufacturing of the extreme ultraviolet light source target according to claim 15, characterized in that the heavy-metal chloride is SnCl_4 .